

View Online at <https://aerobasegroup.com/nsn/5320-01-515-8985>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.510 inches and 2.530 inches

Head Style:

Err-090

Head Height:

Between 0.200 inches and 0.210 inches

Width Between Flats:

Between 0.306 inches and 0.326 inches

Shank Diameter:

Between 0.5766 inches and 0.5771 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.842 inches and 0.877 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10

Grip Length:

Between 1.745 inches and 1.755 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

0.5625 inches

Shear Strength:

65600 double pounds per square inch

Product Name:

Hy-lok

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0