# NSN 5320-01-516-2653

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-516-2653

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

1.047 inches

## Head Style:

Flush countersunk

#### Shoulder Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shoulder Length:

0.502 inches

#### Shank Diameter:

Between 0.3640 inches and 0.3680 inches

#### Shank Style:

Err-090

#### Head Major Diameter:

Between 0.5554 inches and 0.5604 inches

#### Hole Depth:

0.545 inches

# Thready Qty Per Inch (tpi):

24

### Thread Size:

0.375 inches

### **Countersink Angle:**

100.0 degrees

### Material:

Nickel alloy 718

#### **Material Specification:**

Ams 5662 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Hi-shear specification 258 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-516-2653

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

