
# NSN 5320-01-516-2979

Pin-rivet - Page 1 of 2



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.422 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

#### Hole Diameter:

Between 0.0947 inches and 0.0967 inches

#### Shoulder Diameter:

Between 0.2540 inches and 0.2545 inches

#### Shoulder Length:

0.937 inches

#### Shank Diameter:

Between 0.2210 inches and 0.2440 inches

#### Shank Style:

Err-090

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

#### Hole Depth:

Between 0.130 inches and 0.150 inches

#### Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

### Shear Strength:

132000 single pounds per square inch

#### Material:

Cobalt comp mp-35-n

#### Material Specification:

Ams 5758 assn standard single material response or ams 5844 assn standard single material response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

#### Demilitarization:

No



# NSN 5320-01-516-2979

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

