## NSN 5320-01-516-3210

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-516-3210 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.962 inches and 0.982 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches **Hole Diameter:** Between 0.0791 inches and 0.0806 inches **Shoulder Diameter:** Between 0.1940 inches and 0.1945 inches **Shoulder Length:** Between 0.552 inches and 0.572 inches **Shank Diameter:** Between 0.1810 inches and 0.1840 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Hole Depth:** Between 0.115 inches and 0.135 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and dry film Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 132000 single pounds per square inch Material: Cobalt comp mp-35-n **Material Specification:** Ams 5758 assn standard single material response or ams 5844 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-516-3210

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0