NSN 5320-01-517-0694

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-517-0694

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.969 inches

Head Style:

Flush countersunk

Shank Diameter:

0.201 inches

Shank Style:

Pin rivet, threaded

Head Major Diameter:

0.386 inches

Head Minor Diameter:

0.327 inches

Countersink Height:

0.078 inches

End Application:

Aircraft

Thready Qty Per Inch (tpi):

8-56

Thread Size:

0.203 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Criticality Code Justification:

Agav

Product Name:

Pin, adjustable preload, self sustaining, positive mechanical lock, 100 degrees flush head, long thread, inconel 718 (108 ksi fsu)

Special Features:

Grip length is between 1.063 in & 1.125 in

Material:

Nickel alloy

Material Specification:

Inconel 718 per ams 5662 mfr ref single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 military specification single treatment response

Thread Series Designator:

Uns

NSN 5320-01-517-0694

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

spec.

