NSN 5320-01-517-0694

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-517-0694

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
1.969 inches
Head Style:
Flush countersunk
Shank Diameter:
0.201 inches
Shank Style:
Pin rivet, threaded
Head Major Diameter:
0.386 inches
Head Minor Diameter:
0.327 inches
Countersink Height:
0.078 inches
End Application:
Aircraft
Thready Qty Per Inch (tpi):
8-56
Thread Size:
0.203 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Criticality Code Justification:
Agav
Product Name:
Pin, adjustable preload, self sustaining, positive mechanical lock, 100 degrees flush head, long thread, inconel 718 (108 ksi fsu)
Special Features:
Grip length is between 1.063 in & 1.125 in
Material:
Nickel alloy
Material Specification:
Inconel 718 per ams 5662 mfr ref single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 military specification single treatment response
Thread Series Designator:

Uns

NSN 5320-01-517-0694

Pin-rivet - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard): spec.