## NSN 5320-01-517-4263

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-517-4263 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.410 inches and 1.430 inches **Head Style:** Err-090 **Head Height:** Between 0.078 inches and 0.088 inches Width Between Flats: Between 0.197 inches and 0.217 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.565 inches and 0.600 inches Lubrication: Cetyl alcohol **End Application:** C-135 aircraft **Grip Length:** Between 0.870 inches and 0.880 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3750 inches **Shear Strength:** 95000 single pounds per square inch **Product Name:** Bolt, lock Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium

**Surface Treatment Specification:** 

Qq-p-416 type ii class 2 federal specification single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5320-01-517-4263

Pin-rivet - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0