NSN 5320-01-517-4266

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-517-4266 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.500 inches and 1.520 inches **Head Style:** Err-090 **Head Height:** Between 0.093 inches and 0.105 inches Width Between Flats: Between 0.233 inches and 0.253 inches **Shank Diameter:** Between 0.4360 inches and 0.4370 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.641 inches and 0.676 inches Lubrication: Cetyl alcohol **End Application:** C-135 aircraft **Grip Length:** Between 0.870 inches and 0.880 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.4375 inches **Shear Strength:** 95000 single pounds per square inch **Product Name:** Bolt, lock Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium

Surface Treatment Specification:

Qq-p-416 type ii class 2 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-517-4266

Pin-rivet - Page 2 of 2



_						
C	he	14		iŧ	0	•
J			_		ㄷ	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0