NSN 5320-01-517-5911

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-517-5911 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.310 inches and 1.330 inches **Head Style:** Flush countersunk Width Between Flats: 0.170 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.602 inches **End Application:** F-22 **Grip Length:** Between 0.870 inches and 0.880 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3125 inches **Shear Strength:** 19160 double pounds per square inch **Countersink Angle:** Between 99.3 degrees and 100.3 degrees **Product Name:** Rivet, blind Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf Shelf Life:

N/a

NSN 5320-01-517-5911

Pin-rivet - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A528u0