## NSN 5320-01-517-9669

Pin-rivet - Page 1 of 2

**Unit Of Measure:** 



View Online at https://aerobasegroup.com/nsn/5320-01-517-9669 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches **Collar Outside Diameter:** Between 0.408 inches and 0.412 inches Collarheight: Between 0.455 inches and 0.475 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.257 inches and 0.261 inches **Grip Length:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Collar Style:** Threaded break off type Material: Titanium alloy uns r56400 body **Material Specification:** Ams4928 assn standard single material response body or ams4967 assn standard single material response body **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5320-01-517-9669

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0