NSN 5320-01-517-9729

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-517-9729 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.475 inches and 1.495 inches **Head Style:** Flush countersunk Width Between Flats: 0.207 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Head Major Diameter:** 0.524 inches **End Application:** F-22 **Grip Length:** Between 0.995 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3750 inches **Shear Strength:** 27600 double pounds per square inch **Countersink Angle:** Between 99.3 degrees and 100.3 degrees **Special Features:** S" designates spline lock recess Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Thread Series Designator: Unjf Shelf Life: N/a **Unit Of Measure:**

NSN 5320-01-517-9729

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0