# NSN 5320-01-518-0029

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-518-0029



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.045 inches and 1.065 inches

#### Head Style:

Flush countersunk

# Width Between Flats:

Between 0.0791 inches and 0.0806 inches

# Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.266 inches

# End Application:

F22

Grip Length:

Between 0.745 inches and 0.755 inches

# Thready Qty Per Inch (tpi):

32

# Thread Size:

0.1900 inches

#### Shear Strength:

5380 double pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 100.0 degrees

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment:

Phosphate

#### Surface Treatment Specification:

Ams2468 assn standard single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5320-01-518-0029

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

