NSN 5320-01-518-0030

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-518-0030 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.045 inches and 1.065 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Head Major Diameter:** 0.266 inches **End Application:** F22 **Grip Length:** Between 0.745 inches and 0.755 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Shear Strength:** 5380 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees **Special Features:** S"=splinelockrecess Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

NSN 5320-01-518-0030

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0