

View Online at <https://aerobasegroup.com/nsn/5320-01-518-0928>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.675 inches and 2.695 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.269 inches and 0.289 inches

Shank Diameter:

Between 0.5297 inches and 0.5307 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.740 inches and 0.775 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10

Grip Length:

Between 1.995 inches and 2.005 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

95000 pounds per square inch

Thread Size:

0.500 inches

Shear Strength:

42000 double pounds per square inch

Product Name:

Hy-lok

Material:

Steel comp 8740 or steel comp 4140 or steel comp 4340

Material Specification:

Ams-s-6049 assn standard single material response or ams6322 assn standard single material response or ams6382 assn standard single material response or ams6415 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0