## NSN 5320-01-518-1066

Pin-rivet - Page 1 of 2

3a

Err-090

28

Unjf

N/a

---



**Thread Class: Thread Direction: Right-hand Head Style: Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.094 inches and 0.096 inches Shank Diameter: Between 0.2490 inches and 0.2495 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.387 inches and 0.412 inches **Collar Outside Diameter:** Between 0.408 inches and 0.412 inches **Collarheight:** Between 0.455 inches and 0.475 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.257 inches and 0.261 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.250 inches **Collar Style:** Threaded break off type Material: Titanium alloy uns r56400 body **Material Specification:** Ams4928 assn standard single material response body or ams4967 assn standard single material response body **Thread Series Designator:** Shelf Life: Unit Of Measure:



## NSN 5320-01-518-1066

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

