

View Online at <https://aerobasegroup.com/nsn/5320-01-518-1242>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.250 inches and 2.270 inches

Head Style:

Err-090

Head Height:

Between 0.150 inches and 0.160 inches

Width Between Flats:

Between 0.1895 inches and 0.1930 inches

Shank Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.641 inches and 0.676 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10

Grip Length:

Between 1.620 inches and 1.630 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

25800 pounds per square inch

Thread Size:

0.4375 inches

Shear Strength:

37500 single pounds per square inch

Product Name:

Hy-lok

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

-qq-p-416, typeii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0