

View Online at <https://aerobasegroup.com/nsn/5320-01-518-3617>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.712 inches and 0.732 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.311 inches

End Application:

F22

Grip Length:

Between 0.433 inches and 0.443 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2180 pounds per square inch

Thread Size:

0.1640 inches

Shear Strength:

2180 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 100.0 degrees

Special Features:

S" indicates spline lock recess

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Ams2486 assn standard single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0