## NSN 5320-01-518-4468

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-518-4468 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.560 inches and 1.580 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: 0.170 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches **End Application:** F-22 **Grip Length:** Between 1.120 inches and 1.130 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3125 inches **Shear Strength:** 14600 double pounds per square inch **Product Name:** Rivet, blind Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:** 

N/a

Unjf

Shelf Life:

## NSN 5320-01-518-4468

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0