# NSN 5320-01-518-4788

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-518-4788



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.340 inches and 1.360 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

0.132 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.475 inches

#### End Application:

F-22

# Grip Length:

Between 0.995 inches and 1.005 inches

#### Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### Shear Strength:

9300 double pounds per square inch

#### **Countersink Angle:**

Between 99.3 degrees and 100.3 degrees

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment:

Phosphate

## Surface Treatment Specification:

Ams2486 assn standard single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5320-01-518-4788

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

