NSN 5320-01-518-6314

Pin-rivet - Page 1 of 2

Unjf

N/a

Shelf Life:



View Online at https://aerobasegroup.com/nsn/5320-01-518-6314 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.340 inches and 1.360 inches **Head Style:** Flush countersunk Width Between Flats: 0.132 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.475 inches **End Application:** F-22 **Grip Length:** Between 0.995 inches and 1.005 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** Between 99.3 degrees and 100.3 degrees **Special Features:** S" indicates spline lock recess Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:**

NSN 5320-01-518-6314

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0