NSN 5320-01-518-9026

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-518-9026 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.402 inches and 1.422 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.350 inches **End Application:** F22 **Grip Length:** Between 1.057 inches and 1.067 inches Thready Qty Per Inch (tpi): 31 Min. Tensile Strength (psi): 7750 pounds per square inch **Thread Size:** 0.1900 inches **Shear Strength:** 12260 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees Material: Nickel alloy 718 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a Unit Of Measure:

NSN 5320-01-518-9026

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0