## NSN 5320-01-518-9420

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-518-9420 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.402 inches and 1.422 inches **Head Style:** Flush countersunk Width Between Flats: 0.132 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.475 inches **End Application:** F-22 **Grip Length:** Between 1.057 inches and 1.067 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 12260 double pounds per square inch **Countersink Angle:** Between 99.3 degrees and 100.3 degrees **Special Features:** S" indicates spline lock recess Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5320-01-518-9420

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0