NSN 5320-01-518-9734

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-518-9734 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.028 inches and 1.048 inches **Head Style:** Flush countersunk Width Between Flats: 0.132 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.444 inches **End Application:** F-22 **Grip Length:** Between 0.683 inches and 0.693 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** Between 129.3 degrees and 130.3 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-518-9734

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0