## NSN 5320-01-519-0112

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-519-0112 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.590 inches and 1.610 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Head Major Diameter:** 0.475 inches **End Application:** F22 **Grip Length:** Between 1.245 inches and 1.255 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.2500 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-519-0112

Pin-rivet - Page 2 of 2



Fiig:

A528u0