

View Online at <https://aerobasegroup.com/nsn/5320-01-519-0113>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.170 inches and 1.190 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.350 inches

**End Application:**

F22

**Grip Length:**

Between 0.870 inches and 0.880 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

4350 pounds per square inch

**Thread Size:**

0.1900 inches

**Shear Strength:**

7060 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 100.0 degrees

**Special Features:**

S"indicates spline lock recess

**Material:**

Nickel alloy 718

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0