NSN 5320-01-519-0117

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-519-0117 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.872 inches and 0.892 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: 0.170 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Head Major Diameter:** Between 0.475 inches and 0.505 inches **End Application:** F-22 **Grip Length:** Between 0.433 inches and 0.443 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3125 inches **Shear Strength:** 14600 double pounds per square inch **Special Features:** S" indicates spline lock recess Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-519-0117

Pin-rivet - Page 2 of 2



| _ | | | | | |
|----|-----|---------|-----|---|--|
| 11 | em) | tor | 172 | n | |
| | | | | | |

No

Fiig:

A528u0