NSN 5320-01-519-0620

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-519-0620



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.652 inches and 1.672 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.475 inches

End Application:

F22

Grip Length:

Between 1.307 inches and 1.317 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.2500 inches

Shear Strength:

9300 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Ams2486 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-519-0620

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

