

View Online at <https://aerobasegroup.com/nsn/5320-01-519-4197>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.4895 inches and 0.5095 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0791 inches and 0.0801 inches

**Shank Diameter:**

Between 0.1630 inches and 0.1635 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.2564 inches and 0.2612 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

B-2 satcom kit

**Grip Length:**

Between 0.1870 inches and 0.1880 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Shear Strength:**

4010 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0