## NSN 5320-01-519-5656

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-519-5656

Head Style: Universal Head Height: Between 0.054 inches and 0.064 inches Shank Diameter: Between 0.124 inches and 0.128 inches Head Major Diameter: Between 0.238 inches and 0.262 inches End Application: Leading edge Grip Length: Between 0.020 inches and 0.062 inches Material: Aluminum alloy 2017 sleeve Surface Treatment: Anodize stem
Universal  Head Height: Between 0.054 inches and 0.064 inches  Shank Diameter: Between 0.124 inches and 0.128 inches  Head Major Diameter: Between 0.238 inches and 0.262 inches  End Application: Leading edge  Grip Length: Between 0.020 inches and 0.062 inches  Material: Aluminum alloy 2017 sleeve  Surface Treatment: Anodize stem
Head Height: Between 0.054 inches and 0.064 inches Shank Diameter: Between 0.124 inches and 0.128 inches Head Major Diameter: Between 0.238 inches and 0.262 inches End Application: Leading edge Grip Length: Between 0.020 inches and 0.062 inches Material: Aluminum alloy 2017 sleeve Surface Treatment: Anodize stem
Between 0.054 inches and 0.064 inches  Shank Diameter:  Between 0.124 inches and 0.128 inches  Head Major Diameter:  Between 0.238 inches and 0.262 inches  End Application:  Leading edge  Grip Length:  Between 0.020 inches and 0.062 inches  Material:  Aluminum alloy 2017 sleeve  Surface Treatment:  Anodize stem
Shank Diameter: Between 0.124 inches and 0.128 inches Head Major Diameter: Between 0.238 inches and 0.262 inches End Application: Leading edge Grip Length: Between 0.020 inches and 0.062 inches Material: Aluminum alloy 2017 sleeve Surface Treatment: Anodize stem
Between 0.124 inches and 0.128 inches  Head Major Diameter:  Between 0.238 inches and 0.262 inches  End Application:  Leading edge  Grip Length:  Between 0.020 inches and 0.062 inches  Material:  Aluminum alloy 2017 sleeve  Surface Treatment:  Anodize stem
Head Major Diameter:  Between 0.238 inches and 0.262 inches  End Application:  Leading edge  Grip Length:  Between 0.020 inches and 0.062 inches  Material:  Aluminum alloy 2017 sleeve  Surface Treatment:  Anodize stem
Between 0.238 inches and 0.262 inches  End Application: Leading edge  Grip Length: Between 0.020 inches and 0.062 inches  Material: Aluminum alloy 2017 sleeve  Surface Treatment: Anodize stem
End Application: Leading edge Grip Length: Between 0.020 inches and 0.062 inches Material: Aluminum alloy 2017 sleeve Surface Treatment: Anodize stem
Leading edge  Grip Length:  Between 0.020 inches and 0.062 inches  Material:  Aluminum alloy 2017 sleeve  Surface Treatment:  Anodize stem
Grip Length:  Between 0.020 inches and 0.062 inches  Material:  Aluminum alloy 2017 sleeve  Surface Treatment:  Anodize stem
Between 0.020 inches and 0.062 inches  Material:  Aluminum alloy 2017 sleeve  Surface Treatment:  Anodize stem
Material: Aluminum alloy 2017 sleeve Surface Treatment: Anodize stem
Aluminum alloy 2017 sleeve  Surface Treatment:  Anodize stem
Surface Treatment: Anodize stem
Anodize stem
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response sleeve
Specification Data:
80205-nas1398 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-a-8625 spec.