## NSN 5320-01-519-5748

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-519-5748 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.215 inches and 1.235 inches **Head Style:** Flush countersunk **Head Height:** 0.060 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.358 inches **End Application:** F22 **Grip Length:** Between 0.870 inches and 0.880 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 4400 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 12260 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees Material: Nickel alloy 718 **Surface Treatment:** Qq-p-35 federal specification single treatment response

**Passivate Surface Treatment Specification: Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5320-01-519-5748

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0