## NSN 5320-01-519-5809



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-519-5809 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.202 inches and 0.203 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.372 inches and 0.381 inches Lubrication: Dry film and cetyl alcohol **End Application:** Aircraft, hornet f/a-1 (e-f) **Grip Length:** 0.175 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Product Name:** Pin, eddie bolt **Special Features:** Pin, rivet has fluted threads, 100 degrees countersunk tension head and hex point drive Material: Nickel alloy **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5320-01-519-5809

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0