NSN 5320-01-519-5941

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-519-5941 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.685 inches and 0.705 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches **End Application:** F22 **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 12300 pounds per square inch **Thread Size:** 0.3125 inches **Shear Strength:** 19160 double pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal standard single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5320-01-519-5941

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0