NSN 5320-01-519-6795

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-519-6795 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.850 inches and 0.870 inches **Head Style:** Flush countersunk **Head Height:** 0.077 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.524 inches **End Application:** F22 **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 10000 pounds per square inch **Thread Size:** 0.3750 inches **Shear Strength:** 27600 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees Material: Nickel alloy 718 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5320-01-519-6795

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0