

View Online at <https://aerobasegroup.com/nsn/5320-01-519-6795>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.850 inches and 0.870 inches

**Head Style:**

Flush countersunk

**Head Height:**

0.077 inches

**Width Between Flats:**

Between 0.1582 inches and 0.1617 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.524 inches

**End Application:**

F22

**Grip Length:**

Between 0.370 inches and 0.380 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

10000 pounds per square inch

**Thread Size:**

0.3750 inches

**Shear Strength:**

27600 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 100.0 degrees

**Material:**

Nickel alloy 718

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0