

View Online at <https://aerobasegroup.com/nsn/5320-01-520-4416>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.012 inches and 1.032 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.130 inches and 0.140 inches

**Width Between Flats:**

Between 0.1582 inches and 0.1617 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.565 inches and 0.600 inches

**End Application:**

F22

**Grip Length:**

Between 0.683 inches and 0.693 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

14000 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

21000 double pounds per square inch

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Ams2486 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0