## NSN 5320-01-520-9359

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-520-9359

| Violi di ilipon, adi dadadgi dapida ilimon da 20 di 1020 dada                                               |
|-------------------------------------------------------------------------------------------------------------|
| Thread Class:                                                                                               |
| 3a                                                                                                          |
| Thread Direction:                                                                                           |
| Right-hand                                                                                                  |
| Identification Code Color:                                                                                  |
| Yellow                                                                                                      |
| Fastener Length:                                                                                            |
| Between 1.045 inches and 1.065 inches                                                                       |
| Head Style:                                                                                                 |
| Flush countersunk                                                                                           |
| Width Between Flats:                                                                                        |
| 0.112 inches                                                                                                |
| Shank Diameter:                                                                                             |
| 0.189 inches                                                                                                |
| Shank Style:                                                                                                |
| Pin-rivet, straight, threaded                                                                               |
| Head Major Diameter:                                                                                        |
| Between 0.345 inches and 0.352 inches                                                                       |
| Lubrication:                                                                                                |
| Dry film and cetyl alcohol                                                                                  |
| End Application:                                                                                            |
| Used on fighter aircraft (f18-e/f)                                                                          |
| Grip Length:                                                                                                |
| Between 0.745 inches and 0.755 inches                                                                       |
| Thready Qty Per Inch (tpi):                                                                                 |
| 32                                                                                                          |
| Thread Size:                                                                                                |
| 0.190 inches                                                                                                |
| Countersink Angle:                                                                                          |
| Between 99.0 degrees and 101.0 degrees                                                                      |
| Criticality Code Justification:                                                                             |
| Agav                                                                                                        |
| Product Name:                                                                                               |
| Pin, rivet, fluted threads - tension, 100 degrees c'sunk, hex point drive                                   |
| Special Features:                                                                                           |
| Threaded end is chamfered 0.032 inches at 45 degrees; hex drive is 0.0791 to 0.0806 inches across the flats |
| Material:                                                                                                   |
| Titanium alloy                                                                                              |
| Material Specification:                                                                                     |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response          |
| Thread Series Designator:                                                                                   |
| Unjf                                                                                                        |

## NSN 5320-01-520-9359

Pin-rivet - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0