NSN 5320-01-520-9359

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-520-9359

Violi di ilipon, adi dadadgi dapida ilimon da 20 di 1020 dada
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Yellow
Fastener Length:
Between 1.045 inches and 1.065 inches
Head Style:
Flush countersunk
Width Between Flats:
0.112 inches
Shank Diameter:
0.189 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.345 inches and 0.352 inches
Lubrication:
Dry film and cetyl alcohol
End Application:
Used on fighter aircraft (f18-e/f)
Grip Length:
Between 0.745 inches and 0.755 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Criticality Code Justification:
Agav
Product Name:
Pin, rivet, fluted threads - tension, 100 degrees c'sunk, hex point drive
Special Features:
Threaded end is chamfered 0.032 inches at 45 degrees; hex drive is 0.0791 to 0.0806 inches across the flats
Material:
Titanium alloy
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf

NSN 5320-01-520-9359

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0