## NSN 5320-01-520-9501

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-520-9501

| Fastener Length:  |
|---|
| Between 0.818 inches and 0.868 inches   |
| Head Style:   |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)  |
| Shank Diameter:   |
| Between 0.1970 inches and 0.1985 inches   |
| Shank Style:  |
| Threaded self-plugging shank w/sleeve   |
| Head Major Diameter:  |
| 0.385 inches  |
| Lubrication:  |
| Dry film or cetyl alcohol or paraffin wax   |
| End Application:  |
| F-18 e/f hornet aircraft  |
| Grip Length:  |
| Between 0.200 inches and 0.250 inches   |
| Countersink Angle:  |
| Between 99.0 degrees and 101.0 degrees  |
| Material:   |
| Steel comp 303se sleeve   |
| Material Specification:   |
| Ams5732 assn standard single material response bolt or ams5731 assn standard single material response bolt or ams5737 assn standard |
| single material response bolt   |
| Surface Treatment:  |
| Passivate sleeve  |
| Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response sleeve  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Filig:  |
| A040a0  |
|   |