

View Online at <https://aerobasegroup.com/nsn/5320-01-521-0189>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.512 inches and 0.532 inches

**Head Style:**

Flush countersunk

**Shoulder Diameter:**

Between 0.163 inches and 0.164 inches

**Shoulder Length:**

0.210 inches

**Shank Diameter:**

Between 0.157 inches and 0.160 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 0.256 inches and 0.261 inches

**Hole Depth:**

Between 0.115 inches and 0.135 inches

**Collar Outside Diameter:**

Between 0.288 inches and 0.292 inches

**Collarheight:**

Between 0.427 inches and 0.447 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

New man mh-60

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.134 inches

**Countersink Angle:**

100.0 degrees

**Collar Style:**

Threaded break off type

**Special Features:**

Thread class for pin-riquet (body) is 3a; collar inside diameter is 0.166 in (min) and 0.173 in (max)

**Material:**

Steel body

**Material Specification:**

Sae-ams 6322 assn standard single material response body

**Surface Treatment:**

Cadmium body

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0