

View Online at <https://aerobasegroup.com/nsn/5320-01-521-0189>

Thread Class:

3b

Thread Direction:

Right-hand

Fastener Length:

Between 0.512 inches and 0.532 inches

Head Style:

Flush countersunk

Shoulder Diameter:

Between 0.163 inches and 0.164 inches

Shoulder Length:

0.210 inches

Shank Diameter:

Between 0.157 inches and 0.160 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.256 inches and 0.261 inches

Hole Depth:

Between 0.115 inches and 0.135 inches

Collar Outside Diameter:

Between 0.288 inches and 0.292 inches

Collarheight:

Between 0.427 inches and 0.447 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

New man mh-60

Thready Qty Per Inch (tpi):

32

Thread Size:

0.134 inches

Countersink Angle:

100.0 degrees

Collar Style:

Threaded break off type

Special Features:

Thread class for pin-riquet (body) is 3a; collar inside diameter is 0.166 in (min) and 0.173 in (max)

Material:

Steel body

Material Specification:

Sae-ams 6322 assn standard single material response body

Surface Treatment:

Cadmium body

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0