

View Online at <https://aerobasegroup.com/nsn/5320-01-521-0411>

Thread Class:

3b

Thread Direction:

Right-hand

Fastener Length:

Between 0.707 inches and 0.727 inches

Head Style:

Flush countersunk

Hole Diameter:

Between 0.104 inches and 0.119 inches

Shoulder Diameter:

Between 0.189 inches and 0.190 inches

Shoulder Length:

0.392 inches

Shank Diameter:

Between 0.181 inches and 0.184 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.297 inches and 0.302 inches

Hole Depth:

Between 0.104 inches and 0.135 inches

Collar Outside Diameter:

Between 0.303 inches and 0.307 inches

Collarheight:

Between 0.437 inches and 0.457 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Collar Inside Diameter:

Between 0.182 inches and 0.200 inches

End Application:

New man mh-60

Thready Qty Per Inch (tpi):

32

Thread Size:

0.160 inches

Countersink Angle:

100.0 degrees

Collar Style:

Threaded break off type

Special Features:

Thread class for pin-riquet is 3a

Material:

Steel body

Material Specification:

Sae-ams 6322 assn standard single material response body

Surface Treatment:

Cadmium body

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0