

View Online at <https://aerobasegroup.com/nsn/5320-01-521-0411>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.707 inches and 0.727 inches

**Head Style:**

Flush countersunk

**Hole Diameter:**

Between 0.104 inches and 0.119 inches

**Shoulder Diameter:**

Between 0.189 inches and 0.190 inches

**Shoulder Length:**

0.392 inches

**Shank Diameter:**

Between 0.181 inches and 0.184 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 0.297 inches and 0.302 inches

**Hole Depth:**

Between 0.104 inches and 0.135 inches

**Collar Outside Diameter:**

Between 0.303 inches and 0.307 inches

**Collarheight:**

Between 0.437 inches and 0.457 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Collar Inside Diameter:**

Between 0.182 inches and 0.200 inches

**End Application:**

New man mh-60

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.160 inches

**Countersink Angle:**

100.0 degrees

**Collar Style:**

Threaded break off type

**Special Features:**

Thread class for pin-riquet is 3a

**Material:**

Steel body

**Material Specification:**

Sae-ams 6322 assn standard single material response body

**Surface Treatment:**

Cadmium body

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0