## NSN 5320-01-521-0753

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-521-0753



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.482 inches and 0.502 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

0.112 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### **End Application:**

F-22

Grip Length:

Between 0.183 inches and 0.193 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## Shear Strength:

5380 double pounds per square inch

## **Special Features:**

S" indicates spline lock recess

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

## Surface Treatment:

Phosphate

## Surface Treatment Specification:

Ams2486 assn standard single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-521-0753

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

