

View Online at <https://aerobasegroup.com/nsn/5320-01-521-3835>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.079 inches and 0.081 inches

**Shank Diameter:**

Between 0.202 inches and 0.203 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.265 inches and 0.272 inches

**Lubrication:**

Dry film and cetyl alcohol

**Grip Length:**

Between 0.558 inches and 0.568 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Countersink Angle:**

Between 90.0 degrees and 101.0 degrees

**Special Features:**

Fluted threads-shear, 0.0156 oversize, 125 ksi fsu

**Material:**

Nickel alloy 718

**Material Specification:**

Ams-5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0