

View Online at <https://aerobasegroup.com/nsn/5320-01-521-4327>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.678 inches and 0.697 inches

Head Style:

Flush countersunk

Head Height:

Between 0.066 inches and 0.068 inches

Hole Diameter:

Between 0.127 inches and 0.129 inches

Shoulder Diameter:

0.312 inches

Shoulder Length:

0.122 inches

Shank Diameter:

Between 0.302 inches and 0.306 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.438 inches and 0.445 inches

Hole Depth:

0.160 inches

Lubrication:

Cetyl alcohol and dry film or solid film

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Countersink Angle:

100.0 degrees

Special Features:

Lubricant type hi-kote 2 solid film or dry film lubricant per as 5272 (kalgard fa, incotec tec-lube or em620c only) plus cetyl alcohol lubricant per mil-I-87132, (do not spin)

Material:

Titanium alloy uns r56400

Material Specification:

Ams4925 and/or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0