

View Online at <https://aerobasegroup.com/nsn/5320-01-521-5343>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.678 inches and 0.697 inches

**Head Style:**

Flush countersunk

**Shoulder Diameter:**

0.163 inches

**Shoulder Length:**

0.337 inches

**Shank Diameter:**

Between 0.157 inches and 0.159 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 0.237 inches and 0.244 inches

**Lubrication:**

Cetyl alcohol and dry film and solid film

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

Lubricant type hi-kote 2 solid film lubricant or dry film lubricant per as527 (kalgard fa, incotec tec-lub or em620c only) plus cetyl alcohol lubricant per mil-l-87132(do not spin)

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0