NSN 5320-01-521-5433

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-521-5433 **Thread Class:** За Fastener Length: Between 1.115 inches and 1.135 inches **Head Style:** Flush countersunk **Hole Diameter:** Between 0.094 inches and 0.096 inches **Shoulder Diameter:** Between 0.264 inches and 0.265 inches **Shoulder Length:** 0.144 inches **Shank Diameter:** Between 0.241 inches and 0.244 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.358 inches and 0.365 inches **Hole Depth:** 0.140 inches Lubrication: Cetyl alcohol and dry film or solid film Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Special Features:** Lubricant type hi-kote 2 solid film lubricant or dry film lubricant per mil-l-46010 (kalgard fa only) plus cetyl alcohol. Material: Stainless steel **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-521-5433

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0