

View Online at <https://aerobasegroup.com/nsn/5320-01-521-6348>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.287 inches and 1.307 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.078 inches and 0.088 inches

**Width Between Flats:**

Between 0.1582 inches and 0.1617 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.565 inches and 0.600 inches

**End Application:**

F22

**Grip Length:**

Between 0.807 inches and 0.817 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

11300 pounds per square inch

**Thread Size:**

0.3750 inches

**Shear Strength:**

27600 double pounds per square inch

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0