

View Online at <https://aerobasegroup.com/nsn/5320-01-521-9287>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.197 inches and 0.217 inches

**Shank Diameter:**

Between 0.389 inches and 0.390 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.555 inches and 0.560 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.683 inches and 0.693 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

22700 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 8740

**Material Specification:**

Ams-s-6049 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0