NSN 5320-01-522-7544

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-522-7544 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches **Shank Diameter:** Between 0.4047 inches and 0.4057 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.550 inches and 0.585 inches **Collar Outside Diameter:** Between 0.550 inches and 0.585 inches Collarheight: 0.545 inches Lubrication: Cetyl alcohol **Collar Inside Diameter:** Between 0.197 inches and 0.217 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 14000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 24600 double pounds per square inch **Collar Style:** Threaded break off type Material: Steel **Material Specification:** Ams-s-6049 assn standard single material response or ams6322 assn standard single material response or ams6349 assn standard single material response or ams6382 assn standard single material response or ams6415 assn standard single material response **Surface Treatment:** Cadmium

Unjf

Surface Treatment Specification:

Thread Series Designator:

Qq-p-416, type ii, class 2 federal specification single treatment response

NSN 5320-01-522-7544

Pin-rivet - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0